WISI DB 53D

Antenna wall socket SAT/TV/R, 3-ports







Description

The DB 53 D is a 3-ports antenna wall socket for separate connections of radio, TV and satellite receivers. DC bypass at the SAT connector allows feeding power supply and switching commands. The housing offers high stability and ensures high shielding properties (Class A). Low mounting space is required thanks to the flat design of the outlet. The extended F-connector makes sure that patch cable could be easily screwed on.

At a glance:

- 3 pole antenna wall socket
- DC path at the SAT connector
- Robust and low space required die-cast housing
- High screening efficiency according to Class A
- Suitable to the DW 45 D cover and DD 99 D mounting frame
- Suitable for all standard flush-mounted sockets

Wilhelm-Sihn-Str. 5-7 Phone: +49 7233 66-0, Fax-350 75223 Niefern-Oeschelbronn, Germany E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 28. Mai 2024, 10:14 AM

Technical data	
Inputs	
Frequency range	472150 MHz
Outputs	
Frequency range TV	4768/174862 MHz
Frequency range FM	87.5108 MHz
Frequency range-SAT	9502150 MHz
Insertion loss TV	<2 dB
Insertion loss FM	1.5 dB
Insertion loss SAT	<2 dB
Decoupling TV-SAT	≥15 dB (typ. 25 dB)
Return loss TV	≥14 dB @ 5-40 MHz (14 dB -1.5 dB / Octave, ≥10 dB)
Return loss Input	≥18 dB @ 5-40 MHz (18 dB -1.5 dB / Octave, ≥10 dB)
Return loss FM	≥10 dB
Return loss SAT	≥10 dB
Power passing	24 V DC (remote power 500 mA)
Connectors	
Outer conductor clamp	7.5 mm
Inner conductor clamp	0.81.3 mm
F-female	1 pcs.
IEC socket	1 pcs.
IEC-plug	1 pcs.
General data	
Screening factor	>85 dB (class A)
Dimensions (width x height x depth)	70 × 67 × 25 mm
Installation depth	35 mm

Packaging data	
Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	230 x 150 x 75 mm
Packaging volume sales unit	2.6 dm ³
Gross weight sales unit	1.1 kg
EAN	40010056768232
Article number	76823
Customs tariff number	85291095