

WISI DC 28 3S1T

Input splitter



Description

At a glance:

- 3x 7 SAT-outputs, 1x 7 terrestrial outputs
- DC-bypass for the LNB-supply (SAT)
- 19" input distributor for channel processing systems

Technical data

Input	
Numer SAT	21 pcs.
Number TERR	7 pcs.
Frequency range SAT	920...2150 MHz
Frequency range TERR	45...862 MHz
Output	
Output return loss	>12/>15 dB (SAT/TERR)
Through loss	<14/<13 dB (SAT: ±2,5 dB/TERR: ±1 dB)
Decoupling	>23/>25 dB (SAT/TERR)
Connectors	
F-socket	32 pcs.
General data	
Power passing	<21 V DC (only SAT)
Power passing	<1,5 A (only SAT)
Dimensions (width x height x depth)	483 x 44 x 51 mm
Operating temperature range	-20...+55 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.700 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	2.2 dm ³
Gross weight shipping unit	1.7 kg
EAN	4010056712556
Article number	71255
Customs tariff number	85291095