

WISI DD 11 0650

Broadband modem sockets, loop-through sockets (DATA: WICLIC-female)



Description

TV connection with IEC technology. Multimedia with WICLIC-connector for cable modem. HF output high-pass filtered. Cover plate and connector cable see accessories

At a glance:

- Unitymedia certified

Technical data

Inputs

Frequency range 5...1006 MHz

Outputs

Frequency range TV 85...1006 MHz

Frequency range FM 87...1006 MHz

Frequency range DATA 5...1006 MHz

Through loss 3..4 dB

Rejection loss TV ≥ 40 dB 5...65 MHz

Rejection loss FM ≥ 40 dB 5...65 MHz

Insertion loss TV 10 dB

Insertion loss FM 11 dB

Insertion loss DATA 10 dB

Isolation DATA - TV ≥ 70 dB (5...65 MHz)

Isolation DATA - TV ≥ 45 dB (85...1006 MHz)

Isolation DATA - FM ≥ 70 dB (5...65 MHz)

Isolation DATA - FM ≥ 45 dB (85...1006 MHz)

Isolation DATA - OUT ≥ 30 dB (5...1006 MHz)

Isolation FM, TV - OUT ≥ 30 dB (5...1006 MHz)

Return loss IN, OUT ≥ 18 dB (-1.5 dB/oct.)

Return loss TV ≥ 14 dB (-1.5 dB/oct.)

Return loss FM ≥ 14 dB (-1.5 dB/oct.)

Return loss DATA ≥ 18 dB (-1.5 dB/oct.)

Intermodulation ratio > 120 dB μ V (EN60728-4)

Connectors

Outer conductor clamp 7,5 mm

Inner conductor clamp 0,6...1,3 mm

WICLIC female 1

IEC socket 1 pcs. EN60169-2

IEC-plug 1 pcs. EN60169-2

General data

Screening factor > 85 dB (class A)

Dimensions (width x height x depth) 70 x 70 x 22 mm

Installation depth 35 mm

Sales unit 10 pcs.

Dimensions (WxHxD) sales unit 212 x 148 x 78 mm

Packaging volume sales unit dm³

Gross weight sales unit 0.105 kg

Shipping unit 100 pcs.

Dimensions (WxHxD) shipping unit mm

Packaging volume shipping package 0.22 dm³

Gross weight shipping unit 0.11 kg

EAN 4010056108755

Article number 10875

Customs tariff number 85291095