

# WISI DD 15 HP

Broadband modem sockets, Data loop through socket with highpass filter



## Description

TV connection with IEC technology. Multimedia with F-connector or WICLIC for cable modem. HF output high-pass filtered. Cover plate and connector cable see accessories

## At a glance:

- Approved by Vodafone Kabel Deutschland
- Very high decoupling of DATA/TV/Radio connections
- Screwable inner conductor clamp for secure and durable connection

Technical data	
<b>Inputs</b>	
Frequency range	5...862 MHz
<b>Outputs</b>	
Frequency range TV	85...862 MHz
Frequency range FM	87...862 MHz
Frequency range DATA	5...862 MHz
Frequency range loop through	85...862 MHz
Insertion loss TV	14 dB
Insertion loss FM	14 dB
Insertion loss DATA	14 dB
Through loss	1,5...2,5 dB
Isolation DATA - TV	≥40 dB
Isolation DATA - FM	≥40 dB
Isolation DATA-DATA	74 dB (typ.)
Decoupling TV-FM	≥22 dB
Return loss IN	Cat B
Return loss OUT	Cat B
Return loss ALL	Cat C
<b>Connectors</b>	
Outer conductor clamp	7,5 mm
Inner conductor clamp	0,8...1,3 mm
F-female	1 pcs.
IEC socket	1 pcs.
IEC-plug	1 pcs.
<b>General data</b>	
Screening factor	>85 dB (class A)
Dimensions (width x height x depth)	70 x 70 x 22 mm
Installation depth	35 mm
<hr/>	
Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	212 x 148 x 78 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.11 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.24 dm <sup>3</sup>
Gross weight shipping unit	0.11 kg
EAN	4010056193638
Article number	19363
Customs tariff number	85291095