

WISI DD 19 0650

Broadband modem sockets, loop-through sockets



Description

TV connection with IEC technology. Multimedia with WICLIC-connector for cable modem. HF output high-pass filtered. Cover plate and connector cable see accessories

At a glance:

- Unitymedia certified

Technical data	
Inputs	
Frequency range	5...1006 MHz
Outputs	
Frequency range TV	85...1006 MHz
Frequency range FM	87...1006 MHz
Frequency range DATA	5...1006 MHz
Through loss	1,2...1,4 dB
Rejection loss TV	≥40 dB 5...65 MHz
Rejection loss FM	≥40 dB 5...65 MHz
Insertion loss TV	19 dB
Insertion loss FM	19 dB
Insertion loss DATA	19 dB
Isolation DATA - TV	≥70 dB (5...65 MHz)
Isolation DATA - TV	≥50 dB (85...1006 MHz)
Isolation DATA - FM	≥70 dB (5...65 MHz)
Isolation DATA - FM	≥50 dB (85...1006 MHz)
Isolation DATA - OUT	≥30 dB (5...65 MHz)
Isolation FM, TV - OUT	≥30 dB (5...65 MHz)
Return loss IN, OUT	≥18 dB (-1.5 dB/oct.)
Return loss TV	≥14 dB (-1.5 dB/oct.)
Return loss FM	≥14 dB (-1.5 dB/oct.)
Return loss DATA	≥18 dB (-1.5 dB/oct.)
Intermodulation ratio	> 120 dB μ V (EN60728-4)
Connectors	
Outer conductor clamp	7.5 mm
Inner conductor clamp	0,6...1,3 mm
WICLIC female	1
IEC socket	1 pcs. EN60169-2
IEC-plug	1 pcs. EN60169-2
General data	
Screening factor	>85 dB (class A)
Dimensions (width x height x depth)	70 x 70 x 22 mm
Installation depth	35 mm
<hr/>	
Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	212 x 148 x 78 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.105 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.22 dm ³
Gross weight shipping unit	0.11 kg
EAN	4010056108779
Article number	10877
Customs tariff number	85291095