

# WISI DL 100

Surge protector



## Description

Overvoltage protection for coaxial connections, especially for satellite signal distributions, multiswitches and headend systems. With the DL100, all following components are protected from undesirable voltage peaks.

## At a glance:

- Over voltage protection for satellite signal distribution systems
- Overvoltage protection for headends
- Suitable for wideband applications up to 2.4 GHz
- Inline design for easy installation
- Typical application between LNB and multiswitches / headends
- DC loop through

### WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7  
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-0, Fax - 350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. Dezember 2024, 8:30 AM

## Technical data

### Connectors

Input	F-socket / 75 Ohm
Output	F-plug / 75 Ohm
Frequency range	5 ... 2.400
Through loss	0.8 ... 1.2
Return loss	>10 dB
Rated leakage current (8/20 µs)	8 kA
Breakdown voltage 100V/s	230V +/- 42V
Operating voltage	max. 25V
Operating current	max. 1A

### General Data

Dimensions (width x height x depth)	diameter 14 mm / length 48 mm
Weight	0.025 kg
Screening	Class A, according to EN 50083-2

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	14 x 14 x 48 mm
Packaging volume sales unit	0.01 dm <sup>3</sup>
Gross weight sales unit	0.025 kg
EAN	4010056740269
Article number	74026
Customs tariff number	85363010