

WISI DM 02 B

Splitter, 2-way



Description

The DM 02 B is a double distributor which enables the symmetrical division of cable signals on 2 lines. The distribution attenuation is 3.7 dB. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

At a glance:

- Frequency range 5...1000 MHz
- Screening factor according to Class A
- High port isolation and return loss

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

Technical data	
Frequency range	5...1006 MHz
Distribution loss	3.7 dB
Isolation	30 dB
Return loss	18 dB
Connectors	
F-female	3 pcs. (1x input, 2x output)
General data	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	No
Dimensions (width x height x depth)	55x50x28 mm
Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 170 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.06 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.2 dm ³
Gross weight shipping unit	0.06 kg
EAN	4010056702960
Article number	70296
Customs tariff number	85437090