

WISI DM 12 A

SAT splitter, 2-way



Description

The DM 12 A is a double distributor which enables the symmetrical division of antenna signals on 2 lines. The integrated DC bypasses enable the pass-through of distributor voltage. The distribution attenuation is 6 dB. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems.

At a glance:

- Frequency range from 5....2400 MHz
- Parallel distribution of satellite, cable and terrestrial signals possible
- Screening factor according to Class A
- DC-Bypass over every output
- Removable plastic base for cable routing below the distributor
- High port isolation and return loss
- Low distribution loss
- Diode decoupling to avoid short circuits

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

Technical data	
Frequency range	5...2400 MHz
Distribution loss	4...6 dB
Isolation	>20 dB
Return loss	18 dB
Connectors	
F-female	3 pcs. (1x input, 2x output)
General data	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	55x55x28 mm
Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	390 x 310 x 360 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.06 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.2 dm ³
Gross weight shipping unit	0.06 kg
EAN	4010056165772
Article number	16577
Customs tariff number	85437090