

WISI DM 36 A 4024

Four-way tap, 24 dB



Description

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

Technical data

Frequency range	5...1006 MHz
Through loss	0.8 +/- 0.2 dB
Side loss	24 +/- 0.5 dB
Directional attenuation	> 40 / > 33 dB (5...470/470...1000 MHz)
Decoupling	> 33 / > 28 dB (5...470/470...1000 MHz)
Return loss	> 23 dB

Connectors

F-socket	6 pcs. (1x input, 1x run through, 4x branch)
----------	--

General data

Screening factor (EMC)	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	no
Dimensions (width x height x depth)	78 x 58 x 28 mm

Packaging data

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	260 x 155 x 200 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.092 kg
Shipping unit	25 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	8.1 dm ³
Gross weight shipping unit	0.092 kg
EAN	4010056165925
Article number	16592
Customs tariff number	85291095