

WISI DM 51 1010

One-way tap, 11 dB



Description

The DM 51 1010 is a single splitter for cable TV and satellite TV. The insertion loss is 2.5 dB and the tap loss is 11 dB. The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

At a glance:

- Frequency range from 5....2400 MHz
- Parallel distribution of satellite, cable and terrestrial signals possible
- Screening factor according to Class A
- DC-Bypass in the trunk line
- Removable plastic base for cable routing below the distributor
- High port isolation and return loss

Technical data

Frequency range	5...2400 MHz
Through loss	1,5...2,5 dB
TAP loss	11 dB
Directional attenuation	32/25/22 dB (5...40/40...100/100...2400 MHz)
Return loss	18...22 dB

Connectors

F-female	3 pcs. (1x input, 1x run through, 1x branch)
----------	--

General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	52 x 50 x 18 mm

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	360 x 320 x 190 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.06 kg
Shipping unit	200 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	0.06 kg
EAN	4010056165970
Article number	16597
Customs tariff number	85437090