WISI DM 54 A 4010

Four-way tap, 10 dB







Description

The DM 54 A 4010 is a 4-way splitter for cable TV and satellite TV. The insertion loss is according to frequency 3.5/4.5...5 dB (5...862...2400 MHz) and the tab loss is 10 dB. The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

At a glance:

- Frequency range from 5....2400 MHz
- Parallel distribution of satellite, cable and terrestrial signals possible
- Screening factor according to Class A
- DC-Bypass in the trunk line
- Removable plastic base for cable routing below the distributor
- High port isolation and return loss

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7 Phone: +49 7233 66 - 280, Fax: -350

75223 Niefern - Oeschelbronn, Germany E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

Technical data	
Frequency range	52400 MHz
Through loss	3,5/4,55 dB (5862/8622400 MHz)
TAP loss	10/10 dB (5862/8622400 MHz)
Directional attenuation	≥25 dB
Isolation	≥21 dB
Return loss	1822 dB
Connectors	
F-female	6 pcs. (1x input, 1x run through, 4x branch)
General data	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74 x 58 x 18 mm
Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	360 x 320 x 190 mm
Packaging volume sales unit	dm³
Gross weight sales unit	0.15 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.14 dm³
Gross weight shipping unit	0.15 kg
EAN	4010056166038
Article number	16603
Customs tariff number	85437090