

# WISI DM 54 A 4015

Four-way tap, 15/15 dB



## Description

The DM 54 A 4015 is a 4-way splitter for cable TV and satellite TV. The insertion loss is according to frequency 2.5/4.5 dB (5...862/862...2400 MHz) and the tap loss is 15/15 dB (5...862/862...2400 MHz). The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

## At a glance:

- Frequency range from 5...2400 MHz
- Parallel distribution of satellite, cable and terrestrial signals possible
- Screening factor according to Class A
- DC-Bypass in the trunk line
- Removable plastic base for cable routing below the distributor
- High port isolation and return loss

# WISI DM 54 A 4015

Technical data	
Frequency range	5...2400 MHz
Through loss	2,5/4,5 dB (5...862/862...2400 MHz)
TAP loss	15/15 dB (5...862/862...2400 MHz)
Directional attenuation	≥25 dB
Isolation	≥21 dB
Return loss	18...22 dB
Connectors	
F-female	6 pcs. (1x input, 1x run through, 4x branch)
General data	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74 x 58 x 18 mm
Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	360 x 320 x 190 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.08 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	0.08 kg
EAN	4010056166045
Article number	16604
Customs tariff number	85437090