

WISI DM 54 A 4020

Four-way tap, 20/20 dB



Description

The DM 54 A 4020 is a 4-way splitter for cable TV and satellite TV. The insertion loss is according to frequency 1.0/2...2.5 dB (5...862/862...2400 MHz) and the tap loss is 20/20 dB (5...862/862...2400 MHz). The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

At a glance:

- Frequency range from 5...2400 MHz
- Parallel distribution of satellite, cable and terrestrial signals possible
- Screening factor according to Class A
- DC-Bypass in the trunk line
- Removable plastic base for cable routing below the distributor
- High port isolation and return loss

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

WISI DM 54 A 4020

Technical data	
Frequency range	5...2400 MHz
Through loss	1,0/2...2,5 dB (5...862/862...2400 MHz)
TAP loss	20/20 dB (5...862/862...2400 MHz)
Directional attenuation	≥25 dB
Isolation	≥21 dB
Return loss	18...22 dB
Connectors	
F-female	6 pcs. (1x input, 1x run through, 4x branch)
General data	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74 x 58 x 18 mm
Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	360 x 320 x 190 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.08 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	0.08 kg
EAN	4010056166052
Article number	16605
Customs tariff number	85437090