

# WISI DM 54 A 4025

Four-way tap, 25 dB



## Description

The DM 54 A 4025 is a 4-way splitter for cable TV and satellite TV. The insertion loss is according to frequency 0.6/1.8...2.5 dB (5...862/862...2400 MHz) and the tap loss is 25/25 dB (5...862/862...2400 MHz). The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

## At a glance:

- Frequency range from 5...2400 MHz
- Parallel distribution of satellite, cable and terrestrial signals possible
- Screening factor according to Class A
- DC-Bypass in the trunk line
- Removable plastic base for cable routing below the distributor
- High port isolation and return loss

# WISI DM 54 A 4025

## Technical data

Frequency range	5...2400 MHz
Through loss	0,6/1,8...2,5 dB (5...862/862...2400 MHz)
TAP loss	25/25 dB (5...862/862...2400 MHz)
Directional attenuation	≥25 dB
Isolation	≥21 dB
Return loss	18...22 dB

## Connectors

F-female	6 pcs. (1x input, 1x run through, 4x branch)
----------	--

## General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74 x 58 x 18 mm

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	360 x 320 x 19 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.14 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	0.14 kg
EAN	4010056166069
Article number	16606
Customs tariff number	85437090