

# WISI DM 90

SAT splitter



## Description

The DM 90 combines 9 integrated 2 dual splitters in one housing to distribute the signals of 9 reception areas on several strands. The throughput integrated DC-bypass enables the transfer of supply voltage to active components. With its special development it can be easily integrated in multiswitch cascades. High shielding properties (Class A) ensures an interference-free transmission of signals in reception and distribution systems.

## At a glance:

- 2-fold tap for multiswitch cascades
- Distribution of two satellites and terrestrial signals
- 13 dB junctionattenuation

### WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7  
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

## Technical data

Frequency range	5...862/950...2400 MHz (TERR/SAT)
Through loss	1,5...3,0/2...3,5 dB (TERR/SAT)
TAP loss	13...14/14...12 dB (TERR/SAT)
Isolation	35/38 dB (trunk, TERR/SAT)
Return loss	10 dB (min., SAT)

## Connectors

F-female	36 pcs.
----------	---------

## General data

Screening factor	Class A, EN 50083-2
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	210 x 210 x 27 mm

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	255 x 315 x 65 mm
Packaging volume sales unit	dm³
Gross weight sales unit	0.1 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm³
Gross weight shipping unit	kg
EAN	4010056182014
Article number	18201
Customs tariff number	85437090