

WISI DS 40 U 0150

Fly lead F-Quick / F-Quick angled, 1,5 m



Description

IP-based TV and media services require high quality and reliable professional cable solutions. The highly shielded pre-assembled broadband coaxial cable DS 40 U with 1 F-Quick male and 1 angled F-Quick male combines Class A++ (EN 50117) screening with the highest mechanical and technical characteristics for easy and efficient installation in multimedia networks. This powerful Class A++ cable protects data streams perfectly against external sources such as 4G or LTE radio equipment. With a diameter of just 5mm and a bending radius of 30 mm it allows for easy handling by any installer. The cable has a tensile strength of more than 130 N and is further more equipped with Beryllium Copper connections making it extremely robust with superb line properties. Available in lengths of 1.5/3.0/5.0 meters.

At a glance:

- Class A++ > 105 dB (30...1006 MHz)
- Frequency range 5...2400 MHz
- Pre-assembled with 1 F-Quick male and 1 angled F-Quick male
- Length 1,5 meter
- Bending radius: 30 mm
- Tensile strength > 130 N
- UPC certified

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

Technical data

Mechanical Data	
Length	1,5 m
Bend protection	Shrink tube
Breaking stress	>130 N Cable / connector
Bending radius	30 mm
Outer jacket material	PVC black
Outer jacket diameter	Ø 5,00 mm (±0,1 mm)

Cable construction

Inner conductor material	Cu-core
Inner conductor diameter	Ø 0,8 mm (±0,02 mm)
Dielectric	PE
Dielectric diameter	Ø 3,55 mm (±0,05 mm)
Outer conductor 1	AL/Pet bonded
Outer conductor 2	Braid TCCA 24 x 4 x 0,12 (75% coverage)
Outer conductor 3	AL/Pet

Labeling

Character height	3 mm White
Text	(DS40U 0150 105dB WISI YYY,WW)

F-quick connector	(IEC 61169-47)
--------------------------	----------------

F-quick connector angled	(IEC 61169-47)
---------------------------------	----------------

F-quick-male outer conductor	Brass, Plating white bronze. Color code: red ring
------------------------------	---

F-quick-male inner conductor	Brass, (Plating gold)
------------------------------	-----------------------

Pull off / push on force F-quick	≥40 N
----------------------------------	-------

Electrical data

Frequency range	5...2400 MHz
-----------------	--------------

Insertion loss at 1006 MHz	<0,9 dB
----------------------------	---------

Insertion loss at 2400 MHz	<1,3 dB
----------------------------	---------

Return loss 5...12 MHz	>25 dB
------------------------	--------

Return loss 12...300 MHz	>25 dB
--------------------------	--------

Return loss 300...470 MHz	>23 dB
---------------------------	--------

Return loss 470...1006 MHz	>18 dB
----------------------------	--------

Return loss 1006...1700 MHz	>15 dB
-----------------------------	--------

Return loss 1700...2400 MHz	>12 dB
-----------------------------	--------

Transfer impedance 5...12 MHz	≤2,5 mΩ/m
-------------------------------	-----------

Transfer impedance 12...30 MHz	≤0,9 mΩ/m
--------------------------------	-----------

Screen attenuation 30...1006 MHz	>105 dB
----------------------------------	---------

Screen attenuation 1006...2000 MHz	>95 dB
------------------------------------	--------

Screen attenuation 2000...2400 MHz	>85 dB
------------------------------------	--------

Screen class	A++ except 5...12 MHz
--------------	-----------------------

Sales unit	1 pcs. (individual plastic bag)
------------	---------------------------------

Dimensions (WxHxD) sales unit	20x30 mm
-------------------------------	----------

Packaging volume sales unit	dm ³
-----------------------------	-----------------

Gross weight sales unit	kg
-------------------------	----

Shipping unit	250 pcs. (carton)
---------------	-------------------

Dimensions (WxHxD) shipping unit	45x42x30 mm
----------------------------------	-------------

Packaging data

Packaging volume shipping package	dm ³
-----------------------------------	-----------------

Gross weight shipping unit	kg
----------------------------	----

EAN	4010056739096
-----	---------------

Article number	73909
----------------	-------

Customs tariff number	85444210
-----------------------	----------