

WISI FIREFLY GBA02

HLS Streaming IRD for Video Contribution over the Internet.
Up to 2 HLS inputs



Description

FIREFLY HLS RECEIVER is a Smart Broadcast Platform. The Firefly HLS Receiver has been developed specifically to provide an alternative content contribution method. This smart receiver can convert HLS streams to digital formats, and provides a cost-effective solution for operators who wish to distribute linear TV channels to each sub headend. The FIREFLY HLS receiver model GBA02 allows you to receive up to 2 HLS streams, processing, conversion to IP Multicast/Unicast and feeding your digital or analog network.

Scope of delivery

- 1x GBA02
- 1x Quick Guide

At a glance:

- Professional HLS integrated receiver and decoder
- Single or dual HLS stream reception, up to 2x HD sources with 1 profile each or up to 2x SD sources with 1 profile each
- Conversion of HLS to IP Multicast/Unicast
- Intuitive graphical user interface
- Output interface: IP or ASI
- Deployment Scenarios: satellite distribution replacement, hospitality and cable operators, refugees TV, universities

Technical data

HLS Streaming Input

HLS IRD	Up to 2 HLS streams
HLS SD bitrate	Up to 4 Mbps per stream
HLS HD bitrate	Up to 8 Mbps per stream
HLS Adaptive Bitrate (ABR)	No (manual selection)

Streaming- In-/Output

IP-Inputs	32 pcs.
IP-Outputs	32 pcs.
IP-Compliance	ISO/IEC 13818
IP-Input bitrate	Max. 425 Mbit/s per IPTS, Max. 850 Mbit/s total
IP-Output bitrate	Max. 425 Mbit/s per IPTS, Max. 850 Mbit/s total

IP-Input protocol	UDP/RTP/RTP+FEC Unicast and Multicast, IGMP v2 and v3
-------------------	---

IP-Output protocol	UDP/RTP/RTP+FEC Unicast and Multicast, IGMP v2 and v3
--------------------	---

IP-TS-Input format	SPTS CBR/VBR, MPTS CBR
--------------------	------------------------

IP-TS-Output format	SPTS CBR/VBR, MPTS CBR
---------------------	------------------------

IP-FEC Inputs	32 pcs.
---------------	---------

IP-FEC Outputs	32 pcs.
----------------	---------

IP-FEC compliance	SMPTE 2022-1, SMPTE 2022-2
-------------------	----------------------------

IP-Packet format	MPEG over UDP/IP and RTP/IP
------------------	-----------------------------

IP-Packet size	188 Byte
----------------	----------

IP-PCR restamping	Yes
-------------------	-----

IP-Dejittering	Yes, per default 100ms, individual adjustable
----------------	--

ASI Input/Output

ASI-Input/Output	2 pcs. (max.)
------------------	---------------

ASI-Impedance	75 Ω
---------------	-------------

ASI-Frequency range	<270 MHz
---------------------	----------

ASI-Return loss	>17 dB (27...270 MHz)
-----------------	-----------------------

ASI-Compliance	EN 50083-9:2002
----------------	-----------------

ASI-Packet size Input/Output	188, 204/188 Byte
------------------------------	-------------------

ASI-PCR restamping	Yes
--------------------	-----

ASI-Input/Output max. payload bit rate	Typ. 200 Mbit/s
--	-----------------

Processing

Service remultiplexing	Yes
------------------------	-----

PID filtering and remapping	Yes
-----------------------------	-----

PCR correction and de-jitter	Yes
------------------------------	-----

Advanced PSI/SI regeneration	Yes
------------------------------	-----

Processing bitrate	Max. 850 Mbps total
--------------------	---------------------

Number of PIDs	Max. 2000 PIDs total
----------------	----------------------

Compliance	ETSI EN 300 468
------------	-----------------

Connectors

RJ45	3 pcs. (1x Management, 2x Streaming)
------	---

BNC-socket	2 pcs. (Individually configurable for in/out via UI)
------------	--

Technical data

General data

Power consumption	20 W
-------------------	------

Power supply	Redundant power supply, internal, 90...260 V, 47...63 Hz
--------------	---

Operating temperature range	-5°C...+45°C, 23°F...113°F, (ETSI EN 300 019-1-3 Class 3.1)
-----------------------------	--

Max. humidity, non condensing	95 %
-------------------------------	------

Electro Magnetic Compatibility (EMC)	EN 50083-2
--------------------------------------	------------

Safety compliance	CE
-------------------	----

Signalling	Multicolor LEDs (Power on - green, Error - red)
------------	--

Hardware revision	1000
-------------------	------

Software version	-
------------------	---

Packaging data

Sales unit	1 pcs.
------------	--------

Dimensions (WxHxD) sales unit	483 x 45 x 410 mm (1HE, 19"-Rack)
-------------------------------	--------------------------------------

Packaging volume sales unit	dm ³
-----------------------------	-----------------

Gross weight sales unit	kg
-------------------------	----

Shipping unit	1 pcs.
---------------	--------

Dimensions (WxHxD) shipping unit	570 x 100 x 550 mm
----------------------------------	--------------------

Packaging volume shipping package	31,35 dm ³
-----------------------------------	-----------------------