

WISI GI01S4410

INCA 4410 Single-card modular chassis



Description

The extremely flexible WISI platform Inca 4400 for linear & multibitrate transcoding allows network operators to optimize transport streams, manage bandwidth efficiently and monitor their TV and video offers. It supports all operators that wish to extend their offers towards multiscreen applications. They can optimize the formats, resolution and bitrate of large numbers of live satellite, IP and off-air digital sources for delivery to set-top-boxes or multiscreen end devices. Options include modular platforms with up to three bays that can transcode, transrate or downscale up to 36 HD or 90 SD programs to MPEG-4, in just one rack unit of space, with integrated grooming and monitoring of all streams. New are features such as service fail over and high density (up to 128 Audio PIDS) multilingual audio transcode for both ABR and linear applications. WISI now has built VidiOS into every INCA product. VidiOS™ supports the intelligent monitoring and visualization of transport streams at each step of the flow. It also monitors streams that are generated by other equipment. In addition VidiOS supports extensive statistical analysis and provides the operator with an instant overview if a transport stream is available in his network.

At a glance:

- VIDIOS™ stream analysis
- MPEG-4 & MPEG-2 Sources & Outputs
- GigE, 8VSB
- High density linear transcoding
- Multi-Profile ABR
- Adaptive Bitrate Support
- Auto Failover to Backup Services
- Multiple 1RU Chassis Options

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 24. November 2017, 9:52 vorm.

Technical data

Expansion Module Bays

Hardware Transcoding - Linear	Up to 12x HD, 30x SD sources
Hardware Transcoding - ABR	Up to 24x Profiles

VidiOS™ Transport Stream and Video processing

Input and Output	MPEG-2 SPTS/MPTS Transport Stream input, SPTS Output HD & SD, MPEG-2 & MPEG 4 AVC Input and Output Payload Multicast / Unicast UDP IP
Output Streams	48
Transcoded Outputs	up to 30
Direct/Probe Outputs	10 (Optional 48 (4410, 4420, 4430) or 96 (4420,4430))
PID and Program Filter and Remap	Yes
Jitter correction	Yes
Strip Null Padding	Yes
Multiplex Modes	Constant, Variable, Peak
TS Mux Rate VBR <--> CBR Conversion	Yes
Closed Captions	EIA 608/708 passed through if present in source
DVB Subtitle Burn In	Yes
DVB Subtitle PID	Passed through if present in source (can be filtered out)
Data PIDs	Passed through if present in source (can be filtered out)

Management functionality

VidiOS™ Web Based User Interface	Yes
Inca All Seeing Eye Probe Capability	Included
SNMP Trap Forwarding	Yes

Network Interfaces

Management	1000 Base-T
Video	5x 1000 Base-T
NIC Redundancy	Yes (LACP, Active Failover, Round Robin)

Audio Transcode

Source Codecs	AC-3, EC-3, AAC (ADTS & LATM), MPEG-1/2 Audio Layer I/II
Source Channels	7.1, 5.1, 2.0, 1.0
Output Codecs	AAC (ADTS & LATM), MPEG-1/2 Audio Layer I/II
Output Channels	2.0, 1.0
Audio PID Pass-through	Yes

General data

Power supply	Single
Supply voltage	100...240 V AC (50/60 Hz)
Power consumption	typ. <75 W
Montage	19", 2 or 4 Post Rack, 1 RU
Operating temperature range	0...40 °C
EMC Standards	FCC Part 15 Class A
Safety standards	CSA/UL 60950-1

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	431 x 44 x 305 mm (19" x 1,75" x 12")
Packaging volume sales unit	dm³
Gross weight sales unit	4 kg (8.8 lb)
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm³
Gross weight shipping unit	kg
EAN	4010056744335
Article number	74433
Customs tariff number	85176200