

WISI GN 55 W 0048

Additional power supply 48 VDC for redundancy



Description

With the optional power supply GN 55 W 0048 for 48 V, the reliability of the Chameleon platform will be increased significantly - carrier grade. Thanks to the use of the optimised load distribution of redundant power supply, a permanent and reliable supply from a platform is guaranteed. During the operation, even in the case of an error, the PSU can be changed without impairment of the customer signal. Furthermore, the PSU or the complete Chameleon platform can be integrated in a Performance Management Tool. At the PSU the most important parameters (output voltage internal, external, output current, temperature, type, serial number) can be transferred via SNMP.

Scope of delivery

- 1x Power supply 48 V DC
- 1x Quick Guide

At a glance:

- Hot pluggable
- Load sharing with redundant PSU
- Information readable: type, serial number, hardware ID, software ID, max. output power, threshold of max. current, voltage and temperature
- Measure values: output voltage internal, output voltage external, output current, temperature

Technical data

Connectors

Cold-device plug, IEC 60320-C14 0 pcs.

DC-connetors 1 pcs.

General data

Primary voltage -45...-75 V DC

Secondary voltage 12 V DC

Frequency range - Hz

Power consumption 220 W

Efficiency ≥ 90 %

Dimensions (width x height x depth) 100 x 44 x 217 mm

Environmental parameters -20...+55 °C

Protection class IP30

Packaging data

Sales unit 1 pcs.

Dimensions (WxHxD) sales unit 278 x 198 x 86 mm

Packaging volume sales unit dm³

Gross weight sales unit 1.010 kg

Shipping unit pcs.

Dimensions (WxHxD) shipping unit mm

Packaging volume shipping package 4.8 dm³

Gross weight shipping unit 6.46 kg

EAN 4010056722258

Article number 72225

Customs tariff number 85044090