

WISI GN 55 W 0110

Additional power supply 110 VAC for redundancy



Description

In case of failure, the Chameleon power supply unit GN 55 W 0110 the PSU can be changed during the operation without impairment of the customer signals. The PSU, for example, can control and select the most important parameters (output voltage, internal, external, output power, temperature, type, serial no.) via SNMP.

Scope of delivery

- 1x Power supply 110V AC
- 1x Quick Guide

At a glance:

- Hot pluggable
- Load sharing with redundant PSU
- Information readable: type, serial number, hardware ID, software ID, max. output power, threshold of max. current, voltage and temperature
- Measure values: output voltage internal, output voltage external, output current, temperature

Technical data

Connectors

Cold-device plug, IEC 60320-C14 1 pcs.

DC-connetors 0 pcs.

General data

Primary voltage 90...145 V AC

Frequency range 47...63 Hz

Secondary voltage 12 V DC

Power consumption 220 W

Efficiency ≥ 90 %

Dimensions (width x height x depth) 100 x 44 x 217 mm

Environmental parameters -20...+55 °C

Protection class IP30

Packaging data

Sales unit 1 pcs.

Dimensions (WxHxD) sales unit mm

Packaging volume sales unit dm³

Gross weight sales unit kg

Shipping unit pcs.

Packaging volume shipping package 5,6 dm³

Dimensions (WxHxD) shipping unit mm

Gross weight shipping unit 1.01 kg

EAN 4010056744205

Article number 74420

Customs tariff number 85044090