

WISI GT 55 E 0230

Additional power supply 230 VAC for redundancy



Description

With the optional power supply GT 55 E 0230 for 230 V AC, the reliability of the Tangram platform will be significantly increased -carrier grade. Thanks to the use of the optimised load sharing of the redundant power supply, a permanent and reliable supply of the high density platform is guaranteed. During the operation, even in case of an error, the PSU can be changed without impairment of the customer signal. Furthermore, the PSU or the complete Tangram Platform can be integrated in a Performance Management Tool. For the PSU the most important parameters (internal, external output voltage, output current, temperature, type, serial number) can be transferred via SNMP.

Scope of delivery

- 1x Power supply 230 V AC
- 1x Quick Guide

At a glance:

- Hot pluggable
- Load sharing with redundant PSU
- Information readable: type, serial number, hardware ID, software ID, max. output power, threshold of max. current, voltage and temperature
- Measure values: output voltage internal, output voltage external, output current, temperature

Technical data

Connectors

Cold-device plug, IEC 60320-C14 1 pcs.

DC-connectors 0 pcs.

General data

Primary voltage 180...265 V AC

Frequency range 47...63 Hz

Secondary voltage 12 V DC

Power consumption ≤ 278 W

Efficiency ≥ 90 %

Protection class IP30

Max. humidity (non-condensing) 95 %

Operating temperature range -5°C...+45°C, 23°F...113°F,
(ETSI EN 300 019-1-3 Class 3.1)

Electro Magnetic Compatibility (EMC) EN 50083-2

Safety compliance CE

Packaging data

Sales unit 1 pcs.

Dimensions (WxHxD) sales unit 290 x 44 x 217 mm

Packaging volume sales unit 0.95 dm³

Gross weight sales unit 1.06 kg

Shipping unit 1 pcs.

Dimensions (WxHxD) shipping unit 280 x 200 x 90 mm

Packaging volume shipping package 5.3 dm³

Gross weight shipping unit 1.26 kg

EAN 4010056765811

Article number 76581

Customs tariff number 85044090