

# WISI LT 45 S 1530

Optical transmitter module, 1530 nm CWDM



## Description

**WISI Communications GmbH & Co. KG**

Wilhelm-Sihn-Str. 5-7  
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

## Technical data

Laser type	Dual stage isolated DFB laser
Optical output power	+3 dBm
Wave length	1530 nm ( $\pm$ 2 nm)
Frequency range	10 ... 85 MHz
Relative intensity noise	< -145 dB $\sqrt$ /Hz
Nominal input level	75 dB $\mu$ V
Reference pilot	6,8 MHz
Input measurement socket	75 dB $\mu$ V (for 5% OMI)

## Connectors

SC/APC connectors	1 pcs. (Return path-output)
F-socket	1 pcs. (Test port)

## General data

Operating temperature range	-20 ... +55 °C
Storage temperature	-25 ... +75 °C

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	197 x 230 x 75 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.233 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	3.4 dm <sup>3</sup>
Gross weight shipping unit	0.233 kg
EAN	4010056162870
Article number	16287
Customs tariff number	85255000