

WISI LX 55 0048

Power supply unit for LX 50 0048, 48 V DC



Description

The optional 48 V DC power supply LX 55 0048 allows use in the network environment. Thanks to the use of the optimised load sharing of redundant power supply, a permanent and reliable supply of the high density platform is guaranteed. During the operation, even in case of an error, the PSU can be changed without impairment of the customer signal. Furthermore, the PSU or the complete Optopus Platform can be integrated in a Performance Management Tool. For the PSU the most important parameters (internal, external output voltage, output current, temperature, type, serial number) can be transferred via SNMP

At a glance:

- Hot pluggable
- Load sharing with redundant PSU
- Information readable: type, serial number, hardware ID, software ID, max. output power, threshold of max. current, voltage and temperature
- Measure values: output voltage internal, output voltage external, output current, temperature

Technical data

Connectors

Cold-device plug, IEC 60320-C14 1 pcs.

General data

Primary voltage -45...-75 V DC

Secondary voltage 12 V DC

Power consumption 245 W

Efficiency ≥ 90 %

Dimensions (width x height x depth) 100 x 42 x 217 mm

Environmental parameters -20...+55 °C

Protection class IP30

Packaging data

Sales unit 1 pcs.

Dimensions (WxHxD) sales unit mm

Packaging volume sales unit dm³

Gross weight sales unit 0.850 kg

Shipping unit pcs.

Dimensions (WxHxD) shipping unit mm

Packaging volume shipping package 5 dm³

Gross weight shipping unit 0.85 kg

EAN 4010056722272

Article number 72227

Customs tariff number 85044090