

# WISI LXPS B230

Power supply unit for Optopus platform devices, 230 / 110 V AC  
(angled connector)



## Description

The LXPS x230 power supply supports the following Optopus components LX 24, LX 25, LX 52, LX 35 and LX 37 with 230 V or 110 V AC voltage sources.

## At a glance:

- Protection against overload, overheating and short circuit
- Long lifetime thanks to high-performance capacitors
- Distinguished electromagnetic compatibility (EMC)

# WISI LXPS B230

## Technical data

Primary voltage	90 ... 264 V AC (47 ... 63 Hz)
Secondary voltage	12 V DC
Power consumption	< 75 W
Efficiency	≥ 90 %
Dimensions (width x height x depth)	65 x 42 x 200 mm
Environmental parameters	-20 ... +55 °C

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	1.010 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	5,6 dm <sup>3</sup>
Gross weight shipping unit	0,9 kg
EAN	4010056746001
Article number	74600
Customs tariff number	85044090