

WISI MK 76 A 0500

Coaxial cable 115 dB, Ø 5 mm, Length 500 m, PVC white, on plastic drum



Description

The MK 76 A 0500 is a 75 Ohm coaxial cable for the in-house installation. Due to the small diameter of 5 mm, it is perfectly suited for the laying in ductwork or installations with limited space. The triple shielding with a screening efficiency of >115 dB guarantees an interference free transmission in distribution systems for cable TV, terrestrial and satellite signals. The inner conductor consists of pure copper enabling perfect electrical values and a high reliability. With the fire protection class Eca the MK 76 A complies with the Construction Products Regulation (CPR) EU No. 305/2011. The PVC outer sheath is installation friendly and compatible with the WISI connector system as well as commercially available connection accessories.

At a glance:

- Screening class A+ (EN 50117-2-4)
- Screening efficiency > 115 dB
- Triple shielded, bonded outer foil enables easy connector assembly
- Fulfills fire protection class Eca (EN 50575)
- Length indication at the outer sheath
- RoHS compliant
- Ageing resistance, gas foamed dielectric
- Easy installation with WISI connector system (DV 10, DV 10N, DV 50, DV 90)

Technical data

General data

Installation	Indoor installation
Screening factor	Class A+, according to EN 50117-2-4
Color	White
Length	500 m
Reaction to fire	Eca, according to CPR (EN 50575)

Construction

Screening construction	3-way
Inner conductor	Ø 0,80 mm
Insulation	Ø 3,55 mm (Foam PE, gas injected)
Outer conductor 1. Foil	Ø 3,65 mm (Cu)
Outer conductor 2. Braid	58 % (optical coating, tinned copper)
Outer conductor 3. Foil	Aluminium
Sheath	Ø 5,0 mm (PVC, white)

Electrical data

Impedance	75 Ω
Velocity ratio	0,85
DC resistance inner conductor	35,5 Ω/km
DC resistance outer conductor	16 Ω/km
Rated current	5 A
Attenuation 5 MHz	1,9 dB (100 m)
Attenuation 50 MHz	5,7 dB (100 m)
Attenuation 100 MHz	8,1 dB (100 m)
Attenuation 400 MHz	16,5 dB (100 m)
Attenuation 860 MHz	24,7 dB (100 m)
Attenuation 1000 MHz	26,7 dB (100 m)
Attenuation 1400 MHz	31,9 dB (100 m)
Attenuation 2000 MHz	38,6 dB (100 m)
Attenuation 2400 MHz	42,7 dB (100 m)
Attenuation 3000 MHz	48,2 dB (100 m)
Return loss 5...470 MHz	>26 dB
Return loss 470...1000 MHz	>26 dB
Return loss 1000...2000 MHz	>23 dB
Return loss 2000...3000 MHz	>18 dB
Coupling resistance 5...30 MHz	≤1,4 mΩ/m
Screening efficiency 30...1000 MHz	≥115 dB
Screening efficiency 1000...2000 MHz	≥115 dB
Screening efficiency 2000...3000 MHz	≥110 dB

Mechanical Data

Max. permissible force	90 N
Bending radius single/multiple	25/50 mm
Operating temperature	-15...+65 °C
Application temperature range	-5...+50 °C
Copper weight	10,6 kg/km
Total weight	27,92 kg/km

Packaging data

Sales unit	500 m (plastic drum)
Dimensions (WxHxD) sales unit	360 x 370 x 220 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.03 kg
Shipping unit	1000 m (2 x 500 m)
Dimensions (WxHxD) shipping unit	360 x 710 x 220 mm
Packaging volume shipping package	56,23 dm ³
Gross weight shipping unit	kg
EAN	4010056754044
Article number	75404
Customs tariff number	85442000