

WISI MK 86 B 0250

Coaxial cable 110 dB, Ø 6,9 mm, Length 250 m,
PVC white, on plastic drum



Description

The MK 86 B 0250 is a 75 Ohm coaxial cable for the in-house installation. The quality materials and the triple shielding, with a screening efficiency of >110 dB, guarantees an interference free transmission. Thanks to its low cable loss and the perfect installation characteristics, the MK 86 B is ideal for the use in SAT-IF and terrestrial distribution systems. With the fire protection class Eca, the MK 86 B complies with the Construction Products Regulation (CPR) EU No. 305/2011. The PVC outer sheath is installation friendly and compatible with the WISI connector system as well as commercially available connection accessories.

At a glance:

- Screening class A+ (EN 50117-2-4)
- Screening efficiency >110 dB
- Triple shielded, bonded outer foil enables easy connector assembly
- Fulfills fire protection class Eca (EN 50575)
- Length indication at the outer sheath
- RoHS compliant
- Aging resistance, gas foamed dielectric
- Easy mounting with WISI connector system
(DV 15, DV 15N, DV 55, DV 85, DV 95, DV97)

Technical data	
General data	
Installation	Indoor installation
Screening factor	Screening class A+ (EN 50117-2-4)
Color	White
Length	250 m
Reaction to fire	Eca, according to CPR (EN 50575)
Construction	
Screening construction	3-way
Inner conductor	Ø 1.02 mm (CCS)
Insulation	Ø 4,7 mm (Foam PE, gas injected)
Outer conductor 1. Foil	Ø 4.85 mm (AL/PET/SY bonded)
Outer conductor 2. Braid	80 % (AL)
Outer conductor 3. Foil	(AL/PET/SY)
Sheath	Ø 6.9 mm (PVC, white)
Electrical data	
Impedance	75 Ω
Velocity ratio	0.84
DC resistance inner conductor	<100 Ω/km
DC resistance outer conductor	<24 Ω/km
Rated current	8 A
Attenuation 5 MHz	2.4 dB (100 m)
Attenuation 50 MHz	4.3 dB (100 m)
Attenuation 100 MHz	6 dB (100 m)
Attenuation 400 MHz	12.7 dB (100 m)
Attenuation 800 MHz	18.2 dB (100 m)
Attenuation 1000 MHz	20.5 dB (100 m)
Attenuation 1400 MHz	24.5 dB (100 m)
Attenuation 2000 MHz	31.4 dB (100 m)
Attenuation 2400 MHz	32.8 dB (100 m)
Attenuation 3000 MHz	37.4 dB (100 m)
Return loss 5...470 MHz	> 30 dB
Return loss 470...1000 MHz	> 28 dB
Return loss 1000...2000 MHz	> 23 dB
Return loss 2000...3000 MHz	> 17 dB
Coupling resistance 5...30 MHz	≤ 2,5 mΩ/m
Screening efficiency 30...1000 MHz	≥ 110 dB
Screening efficiency 1000...2000 MHz	≥ 100 dB
Screening efficiency 2000...3000 MHz	≥ 97 dB
Mechanical Data	
Max. permissible force	<600 N
Bending radius single/multiple	70/140 mm
Operating temperature	-20...+70 °C
Application temperature range	-10...+60 °C
Total weight	41.5 kg/km

Packaging data	
Sales unit	250 m (plastic drum)
Dimensions (WxHxD) sales unit	350 x 350 x 195 mm
Packaging volume sales unit	24 dm ³
Gross weight sales unit	0.042 kg
Shipping unit	(2 x 250) 500 m
Dimensions (WxHxD) shipping unit	380 x 380 x 415 mm
Packaging volume shipping package	60 dm ³
Gross weight shipping unit	kg
EAN	4010056766207
Article number	76620
Customs tariff number	85442000