

WISI OL 41 0016

Fiber Switch + PSU, 16 outputs



Description

Basic-multiswitch with an optical input, for 16 subscribers.
Conversion of one satellite. Power supply in delivery included.

At a glance:

- Multi switch with optical input
- Upgradeable to 2, 3 or 4 satellite + TV / Radio
- All units operate with only one power supply
- Space-saving design
- 16 subscriber outputs

Technical data

Technical specifications

Frequency range	950...2150 MHz
Impedance	75 Ω
Return loss	10 dB
Output level	80 dBμV Depending on the signal level of the satellites
Signal to noise ratio @ max. amplification	5 dB
SAT decoupling	35 dB

DVB-T, DAB & FM (electric)

Frequency range DVB-T	470...790 MHz
Frequency range DAB	174...240 MHz
Frequency range FM	88...108 MHz
Impedance	75 Ω
Return loss	10 dB
Output level for DVB-T	70 dBμV For 6 multiplexes
Signal to noise ratio @ max. amplification	5 dB
Terrestrial decoupling	30 dB

DVB-T, DAB, FM & SAT (Optic)

Wavelength	1100...1650 nm
Input level	-14...-3 dBm

DC specifications

Input voltage	11...20 V DC
DiSEqC	1

Connectors

Input	FC/PC connector
Outputs	F-female
Power supply	2,1 mm connector
Operating temperature range	-20...+50 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	305 x 205 x 75 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.84 kg
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	305 x 205 x 75 mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	1.84 kg
EAN	4010056745806
Article number	74580
Customs tariff number	85176200