

WISI OL 95 1001

Optical cable term. 1 m



Description

Pre-terminated single-mode fiber optic cables for indoor installations, 1 fiber, FC/PC connector at both sides, length 1 m.

At a glance:

- Low-Smoke-Zero-Halogen-compliant (LSZH)
- Galvanic isolation
- No interferences by electro-magnetic fields
- Integrated protection against tensile strengths and rodents

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

Technical data	
Buffered fiber	
Fiber type	G657A
Outer diameter	0,9 mm
Material	PVC
Typical attenuation	<0,25 dB/km @ 1550 nm; <0,4 dB/km @ 1310 nm
SS tube	
Material	SUS304
Outer diameter	1,65 mm ± 0,05 mm
Width	0,85 mm ± 0,05 mm
Thickness	0,25 mm ± 0,02 mm
Clearance	0,25 mm ± 0,02 mm
Aramid yarn	
Type	1000dtex
Sheath	
Material	LSZH-Compound
Outer diameter	2,9 mm ± 0,05 mm
General data	
Installation	Indoor
Length	1 m
Bending radius	≥ 30 mm
Connectors	
FC/PC	2 pcs.
<hr/>	
Sales unit	1 m
Dimensions (WxHxD) sales unit	170 x 200 x 10 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.032 kg
Shipping unit	1 m
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	0.032 kg
EAN	4010056744021
Article number	74402
Customs tariff number	85447000