

# WISI OL 95 1005

Optical cable term. 5 m



## Description

Pre-terminated single-mode fiber optic cables for indoor installations, 1 fiber, FC/PC connector at both sides, length 5 m.

## At a glance:

- Low-Smoke-Zero-Halogen-compliant (LSZH)
- Galvanic isolation
- No interferences by electro-magnetic fields
- Integrated protection against tensile strengths and rodents

## Technical data

### Buffered fiber

Fiber type	G657A
Outer diameter	0,9 mm
Material	PVC
Typical attenuation	<0,25 dB/km @ 1550 nm; <0,4 dB/km @ 1310 nm

### SS tube

Material	SUS304
Outer diameter	1,65 mm ± 0,05 mm
Width	0,85 mm ± 0,05 mm
Thickness	0,25 mm ± 0,02 mm
Clearance	0,25 mm ± 0,02 mm

### Aramid yarn

Type	1000dtex
------	----------

### Sheath

Material	LSZH-Compound
Outer diameter	2,9 mm ± 0,05 mm

### General data

Installation	Indoor
Length	5 m
Bending radius	≥ 30 mm

### Connectors

FC/PC	2 pcs.
-------	--------

Sales unit	5 m
Dimensions (WxHxD) sales unit	160 x 200 x 20 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.078 kg
Shipping unit	5 m
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	0.078 kg
EAN	4010056744045
Article number	74404
Customs tariff number	85447000