

# WISI OL 95 1075

Optical cable term. 75 m



## Description

Pre-terminated single-mode fiber optic cables for indoor installations, 1 fiber, FC/PC connector at both sides, length 75 m.

## At a glance:

- Low-Smoke-Zero-Halogen-compliant (LSZH)
- Galvanic isolation
- No interferences by electro-magnetic fields
- Integrated protection against tensile strengths and rodents

Technical data	
<b>Buffered fiber</b>	
Fiber type	G657A
Outer diameter	0,9 mm
Material	PVC
Typical attenuation	<0,25 dB/km @ 1550 nm; <0,4 dB/km @ 1310 nm
<b>SS tube</b>	
Material	SUS304
Outer diameter	1,65 mm ± 0,05 mm
Width	0,85 mm ± 0,05 mm
Thickness	0,25 mm ± 0,02 mm
Clearance	0,25 mm ± 0,02 mm
<b>Aramid yarn</b>	
Type	1000dtex
<b>Sheath</b>	
Material	LSZH-Compound
Outer diameter	2,9 mm ± 0,05 mm
<b>General data</b>	
Installation	Indoor
Length	75 m
Bending radius	≥ 30 mm
<b>Connectors</b>	
FC/PC	2 pcs.
<hr/>	
Sales unit	75 m
Dimensions (WxHxD) sales unit	250 x 250 x 170 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	2.02 kg
Shipping unit	75 m
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	2.02 kg
EAN	4010056744106
Article number	74410
Customs tariff number	85447000