

WISI OL 95 2050

optical twin cable term. 50 m



Description

Pre-terminated single-mode fiber optic cables for outdoor use, 2 fibers, PE coating, FC/PC connectors at both ends, length 50 m.

At a glance:

- Special resistant PE-jacket
- UV-resistant
- Galvanic isolation
- No interferences by electro-magnetic fields
- Special gel protect the fibers from damaged caused by water

Technical data

Buffered fiber

Fiber type	G657A
Outer diameter	0,9 mm
Material	LSZH-Compound
Typical attenuation	<0,25 dB/km @ 1550 nm; <0,4 dB/km @ 1310 nm

SS tube

Material	SUS304
Outer diameter	1,65 mm ± 0,05 mm
Width	0,85 mm ± 0,05 mm
Thickness	0,25 mm ± 0,02 mm
Clearance	0,25 mm ± 0,02 mm

Aramid yarn

Type	1000dtex
------	----------

General data

Installation	Outdoor
Length	50 m
Bending radius	≥ 30 mm
Cable weight	45 kg/km

Connectors

FC/PC	4 pcs.
-------	--------

Sales unit	50 m
Dimensions (WxHxD) sales unit	250 x 250 x 170 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	2.52 kg
Shipping unit	50 m
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	2.52 kg
EAN	4010056744137
Article number	74413
Customs tariff number	85447000