

Product information

WISI VX 20 0C 204

Return amplifier for VX 21 0C and VX 22 0C



Description

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

Technical data

Upstream	
Frequency range	5...204 MHz
High pass filter pluggable (optional)	15 MHz (WISI - XE04/0150)
Gain	VX210C 28 dB (± 1 dB), VX220C 32 dB (± 1 dB)
Ripple	$\pm 0,75$ dB
Noise figure	$\leq 6,5$ dB
Output level	> 107 dB μ V (24 x 256 QAM)
Interstage attenuator	0...15 dB (Rotary switch 15 Steps)
Step size	1 dB
Interstage equalizer	0/2/4/6/8 dB (Jumper)
Output attenuator	0/10 dB (Jumper)
Output equalizer	0/6 dB (Jumper)
Ingress control switch (optional)	nach ICS EN 60728-14
Test point	-20 dB

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm ³
Gross weight sales unit	kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	kg
EAN	4010056752859
Article number	75285
Customs tariff number	