

WISI VX 29 BH 82A

Value Line CATV Amplifier, remote powered, 1,2 GHz



Description

The VX29 BH 82A is a remote powered CATV amplifier for distribution applications or in-house installations up to 1.2 GHz. Two integrated switchable diplex filters, with 85 and 204 MHz frequency range, are the perfect solution to be prepared for a future network upgrade. All functional settings (FlexAccess, ALSC, Auto Alignment, Attenuation, Slope, Equalizer, etc.) are adjusted via Bluetooth, using mobile devices or the WISI handheld OH41. The amplifier features an active output and the possibility for upgrading an additional output or loop through input.

At a glance:

- High output level up to 1,2 GHz
- All settings (Gain, slope etc.) via WISI bluetooth App
- Auto Alignment for automatic level adjustment
- Automatic Level and Slope Control (ALSC) with adjustable pilot frequencies
- WISI FlexAccess technology for diplex switchover via Bluetooth or handheld
- Two integrated diplex filters (85 MHz and 204 MHz)
- Interface for optional VT21 module, XM input and output modules
- Optional ICS receiver according to EN 60728-14

WISI VX 29 BH 82A

Technical data

Down-Stream / DS	
Frequency range	108...1218/ 258...1218 MHz (F1/F2)
Noise figure	9 dB
Gain	44 dB ($\pm 0,75$ dB)
Frequency response	$\pm 0,75$ dB
Input attenuator	0...20 dB (0,5 dB steps)
Interstage cable simulator	0/5/10 dB
Interstage attenuator	0...20 dB (0,1 dB steps pivot point 1218 MHz)
Interstage equalizer	0...25 dB (0,1 dB steps)
Interstage Slope	0...15 dB (1 dB steps) / pivot point 1218MHz
Output level	
Output level	110 dB μ V (all QAM (138 x 256 QAM), BER <1e-9, flat)
Output level	112 dB μ V (all QAM (138 x 256 QAM), BER <1e-9, 12 dB slope)
Output level	113 dB μ V (CENELEC 41 Ch. (CSO/CTB > 60 dB), flat)
Output level	115 dB μ V (CENELEC 41 Ch. (CSO/CTB > 60 dB), 12 dB slope)
ALSC Mode	off/one pilot/two pilots Pilot frequency 40...1002 MHz / 0.1 MHz steps
Input test point (bidirectional)	-20 dB ($\pm 1,5$ dB to 858 MHz / ± 2 dB 1218 MHz)
Output test point (directional coupler)	-20 dB ($\pm 0,75$ dB)

Upstream (US)

Frequency range	5...85/5...204 MHz (F1/F2)
Gain	32 dB ($\pm 0,75$ dB)
Frequency response	$\pm 0,75$ dB
Input attenuator	0...15 dB (0,5 dB steps)
Interstage equalizer	0...12 dB (1 dB steps)
Interstage attenuator	0...15 dB (0,5 dB steps)
Noise figure	8 dB
Output level	113 dB μ V ((8 x 256 QAM), BER <1E-9, US 85 MHz)
Output level	107 dB μ V ((24 x 256 QAM), BER <1E-9, US 204 MHz)
NPR >50 dB	>50dB (60 MHz load / -7dBuV / dyn. ≥ 22 dB)
NPR >50 dB	>50dB (192 MHz load / -7dBuV / dyn. ≥ 16 dB)
Ingress Control Switch (ICS)	0/ -6/ <-45 dB (Opt.with Receiver-mod)

General data

RF connectors	PG11
Impedance	75 Ω
In/Output return loss	≥ 18 dB 5...40 MHz; ≥ 18 dB 40...1218 MHz, -1,5 dB/oct. ≥ 12 dB
Input module slot	0 dB Bridge
Output module slot	0 dB Bridge
Universal module slot	-
Supply voltage	27...90 V AC
Power consumption	max. 24 W
Remote power insertion	< 10 A
Remote power current in and bypass	< 10 A
Hum modulation @ 7A, f > 15 MHz	≥ 70 dB
Ambient temperature	-20...+65 °C
Protection class	IP66
EMC	EN50083-2
Surge protection RF Ports	6 kV (1,2/50 μ s pulse EN61000-4-5)

Technical data

Bluetooth functionality	
Downstream configuration	Input attenuator, Interstage attenuator, interstage slope, interstage equalizer, interstage cable simulator, ALSC, FlexAccess
Upstream configuration	Input attenuator, Interstage attenuator, Interstage equalizer, ICS, ALSC, FlexAccess
Options	ICS-Receiver according to EN60728-14 -> VT21, Input/Output modules -> XMx-xB, Ethernet/RF-Modem

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	197 x 86 x 158 mm
Packaging volume sales unit	2.7 dm ³
Gross weight sales unit	1.6 kg
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	285 x 90 x 180 mm
Packaging volume shipping package	4.6 dm ³
Gross weight shipping unit	1.8 kg
EAN	4010056763404
Article number	75811
Customs tariff number	85437030