

WISI VX 87B

In house amplifier, 1 GHz



Description

Locally powered 1 GHz in house amplifier in the compact Mini-Line die-cast housing with a hinged lid for easy access to the adjustment elements.

At a glance:

- Compact housing MiniLine
- All RF connections F-female
- Setting elements with rotary switch
- Flap-lid for easy handling
- Low power consumption

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-0, Fax - 350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 10. März 2025, 1:56 PM

Technical data

Down-Stream / DS

Frequency range downstream	47...1006 MHz
Gain downstream	31 dB
Frequency response	$\leq \pm 0.8$ dB
Output level	≥ 102 dB μ V (CENELEC 42 Ch, flat, CTB/CSO ≥ 60 dB); 99 dB μ V (112 x 256 QAM / BER $\leq 1 \times 10^{-9}$)
IN-ATT (adjuster)	0...20 dB
IN-EQ (adjuster)	0...20 dB
Interstage-EQ (fix)	3 dB
Noise figure	≤ 6.5 dB

General data

HF-connections	F-Female
Impedance	75 Ω
Return loss	≥ 14 dB (>40 MHz - 1.5 dB Oktave ≥ 10 dB)
Lightning protection	1 kV (severity 1 / EN60728-3)
EMC	EN50083-2
Supply voltage	230 V ($\pm 10\%$)
Power consumption max.	≤ 4 W
Ambient temperature	-20...+55 °C
Storage temperature	-25...+75 °C
Protection class	IP20

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	163 x 90 x 50 mm
Packaging volume sales unit	0.7 dm ³
Gross weight sales unit	0.726 kg
Shipping unit	10 pcs.
Dimensions (WxHxD) shipping unit	320 x 230 x 390 mm
Packaging volume shipping package	28.7 dm ³
Gross weight shipping unit	8.76 kg
EAN	4010056767495
Article number	76749
Customs tariff number	85437030