

WISI ZE 15 1200

Cable end plug KES for hKx, 1,2 GHz



Description

High-quality cable end plug with white bronze-coated contact surfaces, for use with coaxial cables with an outer conductor diameter of 12 mm. Can be buried using shrink technology. Tested and approved up to 1.2 GHz, compatible in the complete DOCSIS 3.1 frequency range up to 1.5 GHz.

At a glance:

- Impedance 75 Ohm
- Frequency range up to 1,2 GHz
- Suitable for coaxial cable hKx with Ø 12 mm (outer conductor)
- High-quality materials for ideal electrical properties and a long service life
- Approved by Vodafone Kabel Deutschland
- Approved by Unitymedia

Technical data

Type	Cable end plug KES
Impedance	75 Ω
Through loss	≤ 0,1 dB
Insertion resistance	≤ 2,0 mΩ
Isolation resistance (Inner conductor <-> Outer conductor)	≥ 50 GΩ (1 minute @ 500 V)
Dielectric strength (Inner conductor <-> Outer conductor)	≥ 2 kV (1 minute)
Return loss	≥ 30 dB (5...606 MHz), ≥28 dB(606...1218 MHz)
Screening factor	≥ 85 dB (30...300 MHz) / ≥ 80 dB (300...470 MHz) / ≥ 75 dB (470...1218 MHz)
Transfer impedance	≤ 5,0 mΩ
Rated current	8 A (11 A ≥ 2 h)
General data	
Material	Contact surface white bronze plated (CuSnZn)
Type of mounting construction style	Plugged straight
suitable cable type	Ø 1,8 mm/Ø 12 mm (Inner conductor/Outer conductor) hKx
Dimensions	22 x 22 x 56 mm
DC separation	No

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	135 x 455 x 75 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.032 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.05 dm ³
Gross weight shipping unit	0.032 kg
EAN	4010056752903
Article number	75290
Customs tariff number	85366990